



TEMPEST HP EliteDesk 800 Tower

(Model Number: DTD-800MT-03-L1)

Certification

- NSTISSAM 1-92 Level 1
- NATO SDIP-27 Level A (equivalent)
- CID09/15A (equivalent)



The DTD-800MT-03-L1 is a TEMPEST modified version of the commercially available HP model HP EliteDesk 800 Tower. The DTD-800MT-03-L1 comes configured with an Intel i7-8700, 3.26GHz CPU. The I/O ports include four USB 9-pin DE-9 ports, one (1) 100mbit fiber optic Ethernet port, one audio headset port and two DVI video display out ports. The system also has 16GB of memory. The DTD-800MT-03-L1 has one 256GB Removable Solid State Drive and one DVDRW Drive configured with the system.

All TEMPEST solutions and services available from CIS Secure Computing are CTP II certified by CIS Labs, Inc., a wholly owned subsidiary of CIS Secure Computing, Inc. CIS Labs is a member of the NSA Certified TEMPEST Manufacturer and Test facility program.

Contact Us

CIS Secure Computing, Inc.
21050 Ashburn Crossing Drive
Suite 145
Ashburn, VA 20147

Phone: (703) 996-0500
Fax: (703) 996-1111
eFax: fax@cissecure.com
Website: <http://www.cissecure.com>



TEMPEST HP EliteDesk 800 Tower

Processor	Intel® Core™ i7-8700
Operating System	Windows 10 Pro 64 bit
Memory	16GB, Maximum Memory 64 GB DDR4-2133 SDRAM
Hard Drive	256GB Removable Solid-State Drive (Samsung SSD 860 PRO 256GB)
Integrated Graphics	Intel® UHD Graphics 630
Drive Bay	GS40N 9.5mm Height Ultra Slim Internal DVD
Peripherals	DTD-USBKBD-01-L1 HP USB Keyboard DTD-MSOMUSB-01-L1 USB Microsoft Optical Mouse
Temperature	Operating temperature: 50 °F to 95 °F (10°C to 35°C)
I/O Ports	2 DVI Video Display Output Ports 1 Keyboard and 1 Mouse ports (USB ports (9-pin) DE-9) 1 Headset (Audio) port (9-pin) DE-9 4 - USB 3.0 TEMPEST ports DE-9 – two front, two rear 1-100Mbit Fiber SC Ethernet
Humidity	10 to 90% RH
Dimensions L x W x H	18.75 X 6.75 X 15.75
Power	100/240VAC: 50-60 Hz: 400W: 4A
Weight	15.6 lbs.
Warranty	Standard 1 year parts and labor Optional 3 years parts and labor
Options	DTD-LED24-04-L1 TEMPEST 24" LED Display (up to two displays), - DTD-DVI-D-T6-4 C 6' External DVI-D Single Link Double Cable supplied with monitor DTD-3121T-L1 TEMPEST Omnikey 3121 Card Reader (DE-9 connector) DTD-HSE30-01-L1 TEMPEST Headset with Mic (DE-9 connector) DTD-MCR-02-L1 Media Reader (DE-9 connector) DTD-C920T-04-L1 Logitech C920 HD Webcam (DE-9 connector)