



TSG Approved Analog Phone (Model Number: DTD-ATTEL-01 and DTD-ATTEL-02)



Key Features

- Powered by phone line
- Runs on POTS
- Receiver volume adjustment knob built into handset
- Wall-mounted and desk phones versions

Traditional and uncomplicated, the Analog Wall-Mounted and Desk Phones hook directly up to a plain telephone line. No special setup or extraneous power sources required.

This analog phone is virtually the same as any other touch-tone phone, the only difference being the addition of the Positive Disconnect On-Hook Security. The analog phone is set to automatically disable the on-hook security when the handset is picked up. The phone also allows the on-hook security feature to be engaged while in a call, providing enhanced “hold” and “mute” security. Once the handset is placed back on-hook, the security will engage automatically.

Contact Us

CIS Secure Computing, Inc.
21050 Ashburn Crossing Drive
Suite 145
Ashburn, VA 20147

Phone: (703) 996-0500
Fax: (703) 996-1111
eFax: fax@cissecure.com
Website: <http://www.cissecure.com>



TSG Approved Analog Phone

	Analog Wall-Mounted Phone	Analog Desk Phone
Model Numbers	DTD-ATTEL-01 TSG-NC-01-2018	DTD-ATTEL-02 TSG-NC-02-2018
Power	Provided by phone jack	
Handset	Hearing-aid compatible, 9' cord, variable volume control built-in	
Headset	No headset	
Speakerphone	No speakerphone	
Ports	RJ11 for Telephone Line RJ9 for handset	
Keys	Standard keypad, volume-control	
Ringer Equivalence Number	Type Z	
Licensing	No License required	
Dimensions (H x W X D)	9" x 4 ¼" x 4 ½" (Wall-Mount) 10.2" x 6.5" x 5.8" (Desk)	
Weight	1.7 lbs.	
Temperatures	Operating: 32 to 104°F (0 to 40°C) Non-operating: 14 to 140°F (-10 to 60°C)	
Humidity	10 to 95%, noncondensing	
Warranty	Standard 1 year parts and labor Optional 3 years parts and labor	