



## TSG Cisco 8841 VoIP Phone with Slim Profile

### Key Features

- Retains OEM Profile
  - 5" high resolution widescreen VGA color display
  - Supports a built-in 10/100/1000 Ethernet switch for PC connection
  - Compatible with both IEEE 802.3af and 802.3at switch blades
- Supports 10-line appearances through Enhanced Line Mode feature



### Additional Features

- The speakerphone function is enabled in DTD-8841-06 and DTD-8841-07 and protected with the positive disconnect on-hook security. It can be administratively disabled via the Unified Communications Manager.
- The headset port is enabled and protected with the TSG on-hook security. Any 8841 compatible wired headset may be used. Wireless headsets are not approved for use.



The Cisco 8841 phone supports Session Initiation Protocol (SIP) for signaling, Session Description Protocol (SDP), IPv4, and IPv6. The phone is optimized for use with the Cisco Unified Communications Manager. This Cisco 8841 phone is a modified version that connects to your network like any other 8841 phones. The difference is the addition of Positive Disconnect On-Hook Security. The phone also allows the on-hook security features to be engaged while in a call providing enhanced "Hold" and "Mute" security.

Speakerphone functionality in DTD-8841-06 and DTD-8841-07 is enabled on the device and is protected with the on-hook security of the positive disconnect electronics but can be administratively disabled in the Unified Communications Manager.

The on-hook security can be manually disengaged after an off-hook condition is established (Manual mode) or triggered automatically via the handset hook switch (Auto mode). The mode is set at the factory and must be specified at time of order. The security re-engages automatically once any on-hook status is established.

### Contact Us

CIS Secure Computing, Inc.  
21050 Ashburn Crossing Drive  
Suite 145  
Ashburn, VA 20147

Phone: (703) 996-0500  
Fax: (703) 996-1111  
eFax: [fax@cissecure.com](mailto:fax@cissecure.com)  
Website: <http://www.cissecure.com>



## TSG Cisco 8841 VoIP Phone with Slim Profile

	<b>TSG Compliant Class A</b> Cisco 8841 VoIP Phone	<b>TSG Compliant Class B</b> Cisco 8841 PoE VoIP Phone
<b>Standard</b>	DTD-8841-07 NTSWG# TSG-A-79-2019	DTD-8841-06 NTSWG# TSG-B-73-2019
<b>With Microphone Removed</b>	DTD-8841-07-MR NTSWG# TSG-A-81-2019	DTD-8841-06-MR NTSWG# TSG-B-75-2019
<b>With Speaker Disabled</b>	DTD-8841-07-SD NTSWG# TSG-A-83-2019	DTD-8841-06-SD NTSWG# TSG-B-77-2019
<b>Power</b>	Includes Power Injector required for Class A deployment (DTD-VOIP-PI-02) Input: 100-240vAC, 50-60Hz Output: 48vDC, 0.3a	Power over Ethernet (Standard) Optional OEM Power Supply
<b>Handset</b>	Wideband handset Optional: DTD-88XX-PTT (Push to Talk handset) or DTD-88XX-PTM (Push to Mute handset)	
<b>Headset</b>	Compatible with Plantronics HW510V headset	
<b>Wall Mount</b>	Compatible with Cisco OEM wall mount	
<b>Speakerphone</b>	Full-duplex speakerphone	
<b>LAN and PC Ports</b>	LAN Port: 10/100/1000Mb RJ45 PC Port: 10/100/1000Mb RJ45	
<b>Keys</b>	10 line keys, soft keys, back and release keys, navigation cluster, hold/ resume, transfer, conference, messaging, application, directory, standard keypad, volume-control toggle, speakerphone, headset, mute	
<b>Cisco Unified Communications Manager (CUCM)</b>	8.5.1, 8.6.2, 9.1.2, 10.5.2, 11.0, and later	
<b>Security Features</b>	Secure boot, secure credential storage, device authentication, configuration file authentication and encryption, image authentication, random bit generation, hardware cryptographic acceleration, Certificate Authority Proxy Function (CAPF), Manufacturer-installed Certificates (MIC), Locally Significant Certificates (LSC), Ethernet 802.1x supplicant options: Extensible Authentication Protocol-Flexible Authentication via Secure Tunneling (EAP-FAST) and Extensible Authentication Protocol--Transport Layer Security (EAP-TLS), signaling authentication and encrypting using TLS, media authentication and encryption using SRTP, HTTPS for client and server, Secure Shell (SSH) Protocol server, SSL-based VPN client	
<b>Licensing</b>	The Cisco 8841 requires an Enhanced User Connect License (UCL) to connect to the Cisco Unified Communications Manager. Sold Separately.	
<b>Dimensions (H x W X D)</b>	9.0" x 10.125" x 7" (2.85" without stand)	
<b>Weight</b>	2.8 lbs. (3.3 with Class A Power Injector)	
<b>Temperatures</b>	Operating: 32 to 104°F (0 to 40°C) Non-operating: 14 to 140°F (-10 to 60°C)	
<b>Humidity</b>	10 to 95%, noncondensing	
<b>Warranty</b>	Standard 1 year parts and labor Optional 3 years parts and labor	