



Poly 8300 Conference Phone (Model Number: DTD-TRIO83-01 and DTD-TRIO83-02)

Key Features

- Sleek space saving design
- Easy to operate for superb communication
- Positive Disconnect with LED indicator to show status of security features.



The DTD-TRIO83-01 conference phone is based off the commercially available Poly 8300 Trio conference phone. While in a call, users can control the phone with a secure mute/hold operation with the click of a button, simplifying the method to secure communication and fully demonstrating the capability of the product. The phone is designed to be utilized in conference room environments and is available with external mic pod kits (sold separately) which ensure voice communication during the call is beyond expectation. The DTD-TRIO83 is a must have for companies of any size and any day-to-day operation to achieve success in a technologically advanced working world.

Contact Us

CIS Secure Computing, Inc.
21050 Ashburn Crossing Drive
Suite 145
Ashburn, VA 20147

Phone: (703) 996-0500
Fax: (703) 996-1111
eFax: fax@cissecure.com
Website: <http://www.cissecure.com>



Poly 8300 Conference Phone

| | |
|-------------------------------|---|
| Power | Class B Phone (DTD-TRIO83-01): POE power through LAN port or Local power Class A Phone (DTD-TRIO83-02): Power Injector Included with phone |
| Handset | N/A |
| Headset | N/A |
| LAN-PC-Mic Ports | (1) RJ45 LAN port PC port N/A (2) RJ9 Mic ports |
| Keys | -Soft Keys -Menu cluster keys -Keypad -Call start and end keys -Volume up/down keys |
| Peripherals | RJ45 cable |
| Options | DTD-TRIOPOD-01: External mic kit (sold separately) POWS067: External power supply |
| Dimensions (H x W x D) | 2.5" x 9.5" x 10" |
| Weight | 3 lbs. |
| Temperature | Operating: 32°F to 104°F (0 to 40°C) Non-Operational: -4°F to 160°F (-20°C to 70°C) |
| Humidity | Relative humidity 5% to 95% Non-condensing |
| Warranty | Standard 1-year parts and labor Optional 3-years parts and labor |