CIS Secure Fiber Enabled Phones

When a commercially available Cisco phone with copper connectivity won't meet your requirements, CIS Secure's fiber enabled phones definitely will.







Benefits

Choose from a broad set of Cisco 8841, 8851 and 8865 phones with multiple fiber network connection options (including fiber options not shown in the table)

CIS Secure provides a variety of optional accessories including including push-to-talk handsets and headsets

CIS Secure offers additional options including removable microphone and disabled speakerphone

Product Overview

The CIS Secure fiber enabled phones are a modified version of the commercially available Cisco 8841, 8851 and 8865 phones. These phones supports Session Initiation Protocol (SIP) for signaling for connection to the Cisco Unified Communications Manager as well as support for the Cisco Webex cloud. They offer the same features and functionality supported by manufacturer with the extended capability of connecting to fiber networks.

Part Numbers

Product Number	Model	Mic / Speaker Removed	LAN Port	PC Port
DTD-8841-00A1A	Cisco 8841	No	100 MB SC Fiber	10/100/1000 RJ45
DTD-8841-00B1A	Cisco 8841	No	100 MB LC Fiber	10/100/1000 RJ45
DTD-8841-00B1A-SD	Cisco 8841	Yes	100 MB LC Fiber	10/100/1000 RJ45
DTD-8841-00B3A	Cisco 8841	No	100 MB LC Fiber	100 MB LC Fiber
DTD-8841-00E1A	Cisco 8841	No	1G LC Fiber	10/100/1000 RJ45
DTD-8841-00E1A-SD	Cisco 8841	Yes	1G LC Fiber	10/100/1000 RJ45
DTD-8841-00E5A	Cisco 8841	No	1G LC Fiber	1G LC Fiber
DTD-8851-00E5A *	Cisco 8851	No	1G LC Fiber	1G LC Fiber
DTD-8851-00E5A-NS	Cisco 8851	No	1G LC Fiber	1G LC Fiber
DTD-8865-00E5A	Cisco 8865	No	1G LC Fiber	1G LC Fiber







^{*} Includes Keyboard Expansion Module

CIS Secure TSG Cisco 8841 VoIP Phone

Product Specifications

Handset Port / Headset Port	RJ9 / RJ9 Power Supply (Included)		
Power			
Keys	Line keys, soft keys, back and release keys, four-way navigation and select keys, hold/resume, transfer, mute, conference, messaging, application, directory, headset, standard keypad, volume-control toggle		
Backlit Indicators	Line keys, select key, message waiting, audio path keys (handset and headse		
CUCM	8.5.1, 8.6.2, 9.1.2, 10.5.2, 11.0 and later		
Protocol and Standard Support	Cisco Unified Communications Mgr. (CUCM): 8.6.2, 9.1.2, 10.5.2, 11.0 and late CUCM Express (Unified CME): 10.0 and later through fast track Cisco Business Edition 6000: 8.6.2, 9.1.2, 10.5.2, 11.0 and later Cisco Hosted Collaboration Solution (HCS) / Cisco Webex Standards based SIP Call Control		
Dimensions	9" x 10.125" x 7.25" (H x W x D)		
Weight	4.75 lbs.		
Operating Temp	32°F to 104°F (0° to 40°C)		
Warranty	Standard 1 year parts and labor Optional 3 years parts and labor		

DTD-88XX



