

TSG-approved Poly VVX450 Phone



The CIS Secure TSG-approved DTD-VVX450 allows you to be productive while knowing the phone on your desk is secure.



Benefits

Conversations stay on track. Hear every nuance with industry-leading sound quality featuring Poly HD Voice

Easy deployment and administration with web-based management tools and zero-touch provisioning

Supports VVX Expansion Module and VVX Color Expansion Module (Expandability up to 3 modules)

Product Overview

The Poly VVX450 Business IP Phone delivers engaging communication experiences with a color display and 12-line keys. The phone is a higher-level endpoint option to support both your lines and autodial, also to provide you easy-to-find features. The VVX 450's context-sensitive soft keys provide quick access to functions such as transfer, conference, and call park while on a call. The CIS Secure DTD-VVX450-XX is a modified version that connects to your network like any other Poly VVX450 phone. The difference is the addition of the positive Disconnect On-Hook Security which is controlled by the TSG button.

The CIS Secure DTD-VVX450-XX supports Session Initiation Protocol (SIP), Session Description Protocol (SDP), IPv4, and IPv6. Compliant for use in SCIF and SAPF environments, the phone also allows the On-Hook security features to be engaged while in a call providing enhanced "Hold" and "Mute" security. The additional features of the DTD-VVX450-XX include removable microphone and enable speakerphone protected by the TSG On-Hook security.

Key Features



Twelve Line
Keys



SIP
Capable



Crystal Clear
Sound



4.3" Color
LCD Display



Context-sensitive
Soft Keys



CIS Secure TSG Polycom VVX 450

Product Specifications

	Class A Compliant	Class B Compliant
Part # (Standard)	DTD-VVX450-02 TSG # TSG-A-67-2019	DTD-VVX450-01 TSG # TSG-B-61-2019
Part # (Microphone Removed)	DTD-VVX450-02-MR TSG # TSG-A-69-2019	DTD-VVX-450-01-MR TSG # TSG-B-63-2019
Part # (Speaker Disable)	DTD-VVX450-02-SD TSG # TSG-A-71-2019	DTD-VVX450-01-SD TSG # TSG-B-65-2019
Power	Includes Power Injector required for Class A deployment (DTD-VOIP-PI-02) Input: 100-240VAC, 50-60Hz Output: 48VDC, 0.3A	Power over Ethernet Optional Universal AC Power Supply
RJ9 Headset Port	No	Yes
Handset	Wideband handset	
Speakerphone	Poly HD Voice™ full-duplex speakerphone	
LAN / PC Port	LAN Port 10/100/1000Mb RJ 45 PC Port 10/100/1000Mb RJ 45	
Dimensions (H x W x D)	10" x 9.5" x 2.2" (2.85" without stand)	
Weight	2.25lbs.	
Operating Temp	32°F to 104°F (0° to 40°C)	
Warranty	Standard 1 year parts and labor Optional 3 years parts and labor	