

TEMPEST Cisco Room Bar for Secure Communications



Secure VTC with the positive disconnect capabilities to keep your communications safe and secure.



Benefits

A secure VTC codec with positive disconnect capabilities designed for secure collaboration rooms

Enable flexible deployment scenarios with an endpoint capable of registering to an on-prem Cisco UCM, the Cisco Webex Cloud or Microsoft Teams

Bundled with CIS Secure's TEMPEST certified 42", 55" or 65" flat panel displays to enable a fully compliant TEMPEST VTC solution

Product Overview

The CIS Secure DTD-RMBAR-0X-L1 is a Video Tele Conferencing (VTC) solution designed specifically for customers with secure collaboration requirements. Built on the Cisco Systems Room Bar, the DTD-RMBAR-0X-L1 is a feature rich device when coupled with a compliant CIS Secure flat panel display, delivers the TEMPEST compliant VTC system to meet your needs. This fully integrated platform includes the codec, camera, built-in speakers, and microphone that make it ideal for many collaboration spaces. The DTD-RMBAR-0X-L1 also includes a TEMPEST Cisco Navigator touch panel allowing your teams to maintain an intuitive and consistent end user experience when engaging in meetings and calls.

As the collaboration landscape continues to emerge, the need for flexibility and interoperability are critical factors when deploying VTC technology. With the ability to register to a Cisco UCM, Webex, 3rd party SIP based call control or as native Microsoft Teams Room (MTR), the Cisco Room Bar provides you both flexibility and investment protection. Built by the leader in secure collaboration, the CIS Secure designed DTD-RMBAR-0X-L1 not only delivers TEMPEST compliance, but also provides the positive disconnect capabilities to ensure that the necessary countermeasures are in place to keep your communications safe and secure.

Key Features



Flexible Call Control



HD Camera



Automated Shutter



Table Top Microphone



Dual Monitor Support

✉ sales@cissecure.com

☎ 703-996-0500



TEMPEST Cisco Room Bar for Secure Communications

DTD-RMBAR-0X-L1 Product Specifications

Codec / Display Bundle Part #:	DTD-RMBAR42-0X-L1 Network: 100M LC Fiber / 42" TEMPEST Display DTD-RMBAR42-02-L1 Network: 1G LC Fiber / 42" TEMPEST Display DTD-RMBAR55-0X-L1 Network: 100M LC Fiber / 55" TEMPEST Display DTD-RMBAR55-02-L1 Network: 1G LC Fiber / 55" TEMPEST Display DTD-RMBAR65-0X-L1 Network: 100M LC Fiber / 65" TEMPEST Display DTD-RMBAR65-02-L1 Network: 1G LC Fiber / 65" TEMPEST Display
Video (Content In/Display(s) Out):	(1) LC Fiber / (2) LC Fiber (second display optional)
Audio Input:	(1) DE9 Interfaces - (1) Mic Pod included (25 ft cable)
Audio Output:	(1) ST Fiber port (for use with optional CIS Secure TEMPEST speaker)
Navigator Interface:	(1) LC Fiber
Room Bar SW Compatibility*:	Cisco Systems Unified Communications Manager (UCM) Cisco Webex Cloud Microsoft Teams Room
Codec:	(W x H x D): 25 1/8" x 5 x 4 3/4" / 5.0 lbs
Navigator:	(W x H x D): 10" x 8 1/8" x 3" / 2.3 lbs
Positive Disconnect:	(W x H x D): 5" x 4" x 1" / 0.7 lbs
AC Power:	100-240 VAC:50-60Hz - Power Cord Provided
Operating Temp:	0°C to 40°C (32°F to 104°F) ambient temperature
Warranty:	Standard 1 year parts and labor / Optional 3 years parts and labor

* Based on Cisco published software dependencies and licensing



DTD-RMBAR-0X-L1 Codec - Rear View



Navigator



Positive Disconnect