

# TSG and TEMPEST Cisco Video Collaboration



Secure Video Collaboration on a the Cisco platform while maintaining compliance on your endpoint? You bet!



## Benefits

Leverage our fully integrated VTC codec with TSG-approved positive disconnect capabilities designed for secure collaboration rooms

Enable flexible deployment scenarios with an endpoint capable of registering to an on-prem system or to the Cisco Webex Cloud

Combine with CIS Secure's TEMPEST certified 42", 55" or 65" flat panel displays to enable a fully compliant TEMPEST VTC solution

## Product Overview

The CIS Secure DTD-WXRMKIT-01-L1 is a Video Tele Conferencing (VTC) solution designed specifically for customers with secure collaboration requirements. Based on the Cisco Systems Webex Room Kit, the DTD-WXRMKIT-01-L1 is a full featured device which couples with any flat panel display to deliver a flexible VTC solution. With an integrated camera, codec, speakers, and microphones this video endpoint is ideal for small to medium sized conference rooms. The DTD-WXRMKIT-01-L1 also includes the Cisco Touch 10 providing touchscreen controls when using voice, video and content sharing with the simplicity and intuitive functionality needed to provide a great end user experience.

As an innovator in secure collaboration, CIS Secure designed the DTD-WXRMKIT-01-L1 with the necessary countermeasures to ensure endpoint security. Our secure VoIP and Video endpoints enable our government customers to not only secure their communications but also meet compliance requirements. In September 2021, the National Telecommunications Security Working Group (NTSWG) issued their Annex K amendment to the CNSSI 5000 guidance requiring that all VTC appliances must meet TSG VoIP security requirements. As both a TSG approved and a TEMPEST certified device, the DTD-WXRMKIT-01-L ensures that your VTC environment provides the functionality and compliance you demand.

## Key Features



Touch Screen Controls



HD Camera



Automated Shutter



Table Top Microphone



Dual Monitor Support

✉ [sales@cissecure.com](mailto:sales@cissecure.com)

☎ 703-996-0500



# TSG and TEMPEST Cisco Video Collaboration

## DTD-WXRMKIT Product Specifications

Part #:	DTD-WXRMKIT-01-L1 (100M Fiber) / DTD-WXRMKIT-02-L1 (1G Fiber)
Network Port:	DTD-WXRMKIT-01-L1 - (1) 100M LC / DTD-WXRMKIT-02-L1 - (1) 1G LC
DTD-WXRMKIT-01-L1 TSG #:	TSG-A-01-2023
DTD-WXRMKIT-02-L1 TSG #:	TSG-A-02-2023
Video:	(1) DVI Input / (2) LC Fiber Output
Audio Output:	(2) DE9 Interfaces
Touch 10 Interface:	(1) LC Fiber
Video Standards:	H.264, H.265, and H.263 for TANDBERG™ MXP interoperability only
Audio Standards:	G.711, G.722, G.722.1, G.729, AAC-LD, and Opus
Room Kit SW Compatibility:	CUCM Version 10.5.2 or later Cisco Expressway Cisco Webex Third-party H.323 Gatekeepers and standards-based SIP proxies
Dimensions Codec:	(L x W x H): 18.7 × 4.8 × 5.2"
Dimensions Touch 10:	(L x W x H): 11 × 8.7 × 2.1"
Weight (Codec / Touch 10):	16.2 lbs / 4.5 lbs
AC Power:	100-240 VAC:50-60Hz - Power Cord Provided
Operating Temp:	0°C to 40°C (32°F to 104°F) ambient temperature
Warranty	Standard 1 year parts and labor Optional 3 years parts and labor