



TSG Approved USB Positive Disconnect (Model Number: DTD-TSGPD-01)

Key Features

- Powered by the USB connection or by an optional external 5-volt power supply
- Redundant color LED indicators that signify when it is Safe (green), Live (red). And when Timer expiration is about to occur (blinking of red/blue)
- Analog to USB protocol converter automatically works with no software code needed
- Can be used with a standard stereo headset (3.5mm audio jacks)
- Compatible with any standard wired Cisco or Polycom handset



Additional Features

- Support USB headsets and web cameras
- Integrated time out feature
- Discreet Logic cannot be programmed or reprogrammed
- Includes two hard wired 2-foot USB cables for PC connections

The USB device provides positive disconnect for headsets, soft phone, and web cameras (i.e., Jabber, Skype, and Scopia).

Contact Us

CIS Secure Computing, Inc.
21050 Ashburn Crossing Drive
Suite 145
Ashburn, VA 20147

Phone: (703) 996-0500
Fax: (703) 996-1111
eFax: fax@cissecure.com
Website: <http://www.cissecure.com>



TSG Approved USB Positive Disconnect

TSG Number	TSG-NC-05-2017
Power	Power via USB connection Optional 5VDC power supply
Other Interface	Illuminated dome (Green indicates lines are secure, Red indicates lines are unsecure, alternating Blue/ Red indicates auto-enabling of security is imminent)
Temperature	Operating: 40 to 95°F (5 to 35°C) Non-operating: -13 to 140°F (-25 to 60°C)
Humidity	Operating: 8 to 85%, noncondensing Non-operating: 8 to 90% noncondensing
Dimensions (H x W x D)	4.25" x 1.875" x 3.75"
Weight	0.5 lbs.
Warranty	Standard 1-year parts and labor Optional 3 years parts and labor